

# ONDUVILLA® APRON PIECE

## TECHNICAL DATA SHEET

### APPLICATION

The APRON PIECE is mainly used in the ridge system of ONDUVILLA®, to secure appropriate watertightness and ventilation of the ridge line

Designed as a multi purpose element, it is also used:

- as a junction element between ONDUVILLA® tiles and vertical wall abutment
- in the case of a slope change (as an alternative to our sealing tape FLASHING BAND).

### TECHNICAL CHARACTERISTICS

Made of cellulosic fibers, natural pigments and bitumen.  
Manufactured using molding process (patented technology).

Length	102 cm
Width	14 cm
Height of corrugation	4 cm
Thickness	2,2 mm
Weight (pigmented/painted)	0,36 / 0,38 kg

### PACKAGING

Full range matching all ONDUVILLA® colours (pigmented/painted).  
Box 20 pcs  
Pallet 28 boxes (560 pcs)

### HANDLING AND STORAGE

The product should be protected from direct sunlight and be stored dry.

### INSTALLATION

Used at ridge for roofs with a pitch up to 120% (50°). For pitches between 70% and 120%, it is necessary to cut the flat part above the corrugations.

A gap of 1 cm is necessary between both APRON PIECES, in order to ensure appropriate ventilation.

When used as a wall abutment, the ventilation gap between the wall and the APRON PIECE is also necessary. Watertightness is secured by using an aluminium Z-profile and a line of silicon mastic.



For specific roof details, please refer to ONDUVILLA® fixing guide.

This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company.

#### ONDULINE AVRASYA

Değirmen Sokak Nida Kule İş Mrk.  
No:18 Kat:8 34742 Kozyatağı, Kadıköy/ İSTANBUL  
Tel.: +90 216 384 16 00 pbx.  
Fax: +90 216 384 16 10

www.onduline.com.tr



### WARRANTY

Watertightness is guaranteed for 15 years.

All the claims will be considered with respect to application recommendations issued by Onduline company.

**Onduline®**